
ITE-SHOP
By professionals for professionals

TECHNICAL DATA SHEET

Compribande

Reference - 0310/1-4 à 0320/4-9



SCOPE OF APPLICATION

Expansion joints between masonry and concrete to separate the supports from each other when intalling windows or insulating panels.

DIMENSIONS

Reference	0310/1-4	0310/2-6	0310/2-6
Width	10 mm	10 mm	20 mm
Compressed thickness	~2 mm	~3 mm	~4 mm
Joint width	1- 4 mm	2 - 6 mm	4 - 9 mm
Roll length	13 m	12 m	8 m

INDICATIONS

Depending on temperature conditions, the expansion behaviour may fluctuate (do not store in direct sunlight !). The substrates msut be free of dust, grease and other contaminants. Don't stretch the tape !

TECHNICAL DATA

Packaging per carton	0310/1-4 : 25 rolls 0310/2-6 : 16 rolls 0310/2-6 : 12 rolls
Thermal conductivity	λ10 = 0.055W/(m · K) - DIN 52 612
Air permeability	a <0.1 m³/(h·m·(daPa) - DIN 18 542
Fire classification	B1, flame retardant - DIN 4102, part1
Temperature resistance	-30°C to 90°C
Compatibility	Good compatibility with adjacent building materials - DIN 18542
Shelf life	1 year in a dry place and in its original packaging
Storage temperature	10°C to 20°C
Material	Precompressed foam sealing strip
Color	Anthracite
Weight by volume	150 g/m²

Géo Technic - Impasse Teynier 31100 TOULOUSE
www.ite-shop.com - contact@ite-shop.com
SAS with a capital of 100 000 € - SIRET : 532 890 290 00051 - NAF : 4673A